

XBO 3000W/HS XL OFR



Product features and benefits

- High luminance (point source)
- Color temperature approximately 6000K simulates daylight
- Continuous spectrum in the visible range
- High color rendering > 95
- High arc stability
- DC operation
- Hot restart
- Long lamp life with eXtreme Life technology

Areas of application

- Digital
- Film Projection
- Spotlights
- Searchlights
- Solar Simulation

Technical data

General product information

Product Number	69479			
Product Name	XBO3000WHSXLOFR 1/CS 1/SKU			
Ordering Abbreviation	XBO 3000W/HS XL OFR			
Brand Name	OSRAM			
Family Brand Name	ХВО			
General Description	3000 Watt Xenon High Pressure Cinema Film Projection Lamp - Xteme Life			
Application	Cinema Film Projection			
Product Remark	 S=Short OFR=Ozone Free s (Operating Position) = Vertical, base down p (Operating Position) = Horizontal Magnetic arc stabilization: necessary for horizontal operation This lamp has positive pressure even when cold. Please read safety/warning instructions before using this lamp. XL=Xtreme Life 			

Nominal Wattage	3000 W
Nominal Voltage	29 V
Current (A)	100 A
Current Control Range (A)	60-110 A
Type of Current	DC

Light technical data

Light Center Length - LCL (mm)	145 mm
Warranty Hours (hr)	2200 hrs

Physical attributes

Base Anode	SFaX27-9.5
Base Cathode	SFa27-7.9
Bulb Shape	К0162
Maximum Overall Length (mm)	342 mm
Length l1 max. (mm)	342 mm
Length l2 max. (mm)	302 mm
Diameter d (in)	2.362 in

Product datasheet

Diameter d (mm)	60.00 mm
Distance a (mm)	145 mm
Electrode Gap - cold (mm)	6 mm
Reflector Coating	60.00

Additional product data

Operating Position	s15 p15
Maximum Base Temperature (°C)	230 C
Cooling	Required
Class	C (gas)

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
69479	4062172030311	Shipping box (Case)	1	19.7 in x 8 in x 8 in	3.3 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

- OSRAM does not accept liability for errors, changes and omissions.