

XBO 7000 W/HS XL OFR

XBO | Xenon short-arc lamps 450...10,000 W



Areas of application

- Classic 35 mm film projection
- Digital film and video projection
- Architectural and effect light ("Light Finger")
- Sunlight simulation

Product family benefits

- Short arc with very high luminance for brighter screen illumination
- Constant color temperature of 6,000 K throughout the entire lamp lifetime
- Easy to maintain
- High arc stability
- Instant light on screen thanks to hot restart function
- Wide dimming range

Product family features

- Color temperature: approx. 6,000 K (Daylight)
- Wattage: 450...10,000 W
- Very good color rendering index: $R_a >$




Product datasheet

Technical data

Electrical data

Nominal current	160 A
Lamp current	160 A
Current control range	110...165 A
Nominal wattage	7000.00 W
Nominal voltage	42.0 V

Dimensions & weight



Diameter	78.0 mm
Length	436.0 mm
Length with base excl. base pins/connection	393.00 mm
Light center length (LCL)	170.5 mm ¹⁾
Cable/wire length, input side	400 mm
Electrode gap cold	11.0 mm
Product weight	1025.00 g
Cable length	400.0 mm

¹⁾ Distance from end of base to tip of electrode (cold)

Temperatures & operating conditions

Max. permitted ambient temp. pinch point	230 °C
--	--------

Lifespan

Lifespan	650 h
----------	-------

Additional product data

Base anode (standard designation)	SFaX30-9.5
Base cathode (standard designation)	SFa30-7.9

Product datasheet

Capabilities

Cooling	Forced ¹⁾
Burning position	p15 ²⁾

¹⁾ Vertical and horizontal

²⁾ For vertical burning position: anode (+) on top

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172030625	XBO 7000 W/HS XL OFR	Shipping carton box 1	590 mm x 234 mm x 234 mm	32.31 dm ³	2331.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.