

## HBO 2001 W/CIL

HBO-IC | Microlithography lamps for Canon i-line systems




# Product datasheet

## Technical data

### Electrical data

Nominal current	77 A
Nominal voltage	26 V
Type of current	DC
Rated wattage	2000.00 W
Nominal wattage	2000.00 W

### Dimensions & weight



Diameter	62.0 mm
Length	309.0 mm
Mounting length	309.0 mm
Electrode gap cold	4.5 mm

### Capabilities

Dimmable	No
Burning position	Other <sup>1)</sup>

<sup>1)</sup> Anode on top

## Product datasheet

---

### Safety advice

Because of their high luminance, UV radiation and high internal pressure (when hot) HBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. More information is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

---

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300947235	HBO 2001 W/CIL	Folding carton box 1	605 mm x 320 mm x 230 mm	44.53 dm <sup>3</sup>	3036.00 g
4050300965901	HBO 2001 W/CIL	Folding carton box 4	- x - x -		
4050300627571	HBO 2001 W/CIL	Shipping carton box 4	800 mm x 600 mm x 824 mm	395.52 dm <sup>3</sup>	20603.00 g

---

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

- Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.