

HBO 201 W/HS-D2

Other microlithography lamps up to 1,000 W




Technical data

Electrical data

Nominal voltage	25.0 V
Nominal current	8.00 A
Type of current	DC
Rated wattage	200.00 W
Nominal wattage	200.00 W

Dimensions & weight



Diameter	20.0 mm
Length	150.0 mm
Electrode gap cold	2.0 mm

Capabilities

Dimmable	No
Burning position	Other ¹⁾

¹⁾ Anode on top

Product datasheet

Safety advice

Because of their high luminance, UV radiation and high internal pressure (when hot) HBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. More information is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300591940	HBO 201 W/HS-D2	Folding carton box 1	205 mm x 59 mm x 92 mm	1.11 dm ³	199.67 g
4050300591957	HBO 201 W/HS-D2	Shipping carton box 10	471 mm x 172 mm x 216 mm	17.50 dm ³	2186.00 g
U	HBO 201 W/HS-D2		- x - x -		

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.