

## HBO 4301 W/NHL

HBO-IC | Microlithography lamps for Nikon LCD systems




# Product datasheet

## Technical data

### Electrical data

Nominal voltage	62.0 V
Nominal current	69.0 A
Type of current	DC
Rated wattage	4300.00 W
Nominal wattage	4300.00 W

### Dimensions & weight



Diameter	80.0 mm
Length	389.0 mm
Electrode gap cold	5.0 mm

### Capabilities

Dimmable	No
Burning position	Other <sup>1)</sup>

<sup>1)</sup> Anode on top

## Product datasheet

---

### Safety advice

Because of their high luminance, UV radiation and high internal pressure (when hot) HBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. More information is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

---

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321378408	HBO 4301 W/NHL	Shipping carton box 1	800 mm x 600 mm x 953 mm	457.44 dm <sup>3</sup>	17355.00 g
4008321378415	HBO 4301 W/NHL	Shipping carton box 1	605 mm x 320 mm x 230 mm	44.53 dm <sup>3</sup>	2980.00 g
4008321378422	HBO 4301 W/NHL	Shipping carton box 4	800 mm x 600 mm x 953 mm	457.44 dm <sup>3</sup>	26669.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

- Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.